

TECH SHEET

CyclingCeramic Bottom Bracket (BB)

Spacer Overview for SRAM DUB

CYCLINGCERAMIC

ROAD / GRAVEL BB Standard	Frame width (mm)	Standard (93 mm)		Wide (98 mm)	
		Non-drive	Drive	Non-drive	Drive
BB30	68	0 mm	2 mm	2 mm	4.5 mm
BB86	86.5	0 mm	2 mm	2 mm	4.5 mm
BBright	79	0 mm	2 mm	2 mm	4.5 mm
PF30	68	0 mm	2 mm	2 mm	4.5 mm
BSA	68	0 mm	2 mm	2 mm	1.5 mm
EVO386	86.5	0 mm	2 mm	2 mm	4.5 mm
ITA	70	0 mm	2 mm	2 mm	4.5 mm
T45 (Colnago)	82.5	0 mm	2 mm	2 mm	4.5 mm
T47	68 / 86.5	0 mm	2 mm	2 mm	4.5 mm
T47.	77	0 mm	2 mm	2 mm	1.5 mm

Width	Spacers
2 mm	2 mm
4.5 mm	4,5 mm

Because of manufacturing tolerances and variations between frames and cranksets, it is recommended to always verify alignment and clearances after tightening the cranks to the specified torque and before riding. This spacer guide is intended as a general reference for standard configurations and may require individual adjustments depending on the specific combination of components used.